GLX Green 5mW Tactical Laser Sight w/Picatinny Rail

DESCRIPTION

The BARSKA 5mW Green Laser Sight GLX features external riflescope style windage and elevation (W/E) adjustments for quick, high precision targeting. Zeroing in your laser is a quick and easy process. The tactical design integrates a tactical edged bezel into the strong T6 aluminum body for added protection. The diamond cut exterior grip improves the mounting capability of the picatinny 1" mounting ring included with the laser sight.

WARNING: BE CERTAIN THAT YOUR FIREARM IS NOT LOADED AND POINTED AWAY FROM YOU IN A SAFE DIRECTION
ATTENTION: THIS BARSKA LASER SIGHT IS A POWERFUL TARGETING DEVICE THAT REQUIRES SPECIAL ATTENTION WHEN OPERATING. CAREFULLY READ THE FOLLOWING INSTRUCTIONS AND SAFETY PRECAUTIONS BEFORE USING THIS PRODUCT.
CAUTION: UNAUTHORIZED USE MODIFICATIONS OF ADJUSTMENTS OR PERFORMANCE OF PROCEDURE OTHER THAN SPECIFIED HEREIN MAY RESULT IN DANGEROUS/HAZARDOUS RADIATION EXPOSURE.
LASER LIGHT: AVOID DIRECT EYE EXPOSURE.

WARNING KEEP OUT OF REACH OF CHILDREN.

DO NOT POINT LASER AT PEOPLE, PETS, AIRPLANES, SHINY/HIGHLY REFLECTIVE SURFACES, OR ANY OTHER OBJECT NOT INTENDED FOR DESIGNATED USE.

MOUNTING

Your laser sight is equipped with a Picatinny Rail. This rail will attach your laser to your firearm.

1. Slide the laser sight into the bore of the Picatinny rail.
2. Once the sight is in the rail tighten it in place by using an Allen wench.
3. Slide the rail onto your firearm, then tighten it in place.

BATTERY

This device is powered by one 3v (CR 123A) Lithium Battery.
1. Unscrew the cable switch by turning it counter clockwise
2. Insert the battery so that the positive pole of the battery faces out.
3. Replace the switch back on the laser sight. Turn clockwise to tighten the cable switch onto the sight. Make sure that you have screwed the switch on tightly.

WINDAGE & ELEVATION

Adjustments must be made in the shooter's position of the sight. This laser sight has been factory calibrated. Should you require adjusting the windage and elevation remove turret caps and see chart below to distinguish which of these knobs you need to turn and in which direction.



	Up	Down	Left	Right
Elevation	C	CC		
Windage			CC	C

CC: Counter Clockwise
C: Clockwise

ACCESSORIES INCLUDED

- Continuous push button on/off cap
- 1" picatinny rail ring with removable cross-bar
- Momentary on/off long cable switch

TECHNICAL DATA

Visible Laser Class IIIA Laser Product

Length	138mm
Weight	204g
Main Tube Diameter	1 inch
Output Power	<5mW
Wavelength	532(±10)nm
Reach	1000 YDS
Adjustment	Windage & Elevation
Material	T6 Aluminum
Battery Type	CR-123A Lithim

WARNING:
AVOID EXPOSURE LASER RADIATION IS EMITTED FROM THIS APERTURE
DANGER
LASER RADIATION AVOID DIRECT EYE EXPOSURE

Max Output<5mW
WAVELENGTH 532(±10)nm
Class IIIA Laser Product
FDA NO.:0720007

This product complies with 21 CFR chapter 1, subchapter L.

5mW Green Laser Sight
Model: AU11404
Made In China
Manufactured on 01/2010

BARSKA Optics
1721 Wright Ave,
La Verne CA, 91750 USA

BC148 1/2010

© 2010 BARSKA® La Verne, CA 91750, USA
www.barska.com